

# FR 795 SCC OE SMT

Over Extension Progressive Action Drawer Slide



## Specifications

- side mount
- 18.0 mm / 0.71 in.
- dynamic up to 60 kg / 132 lbs.
- solid synthetic rollers
- stainless steel 1.4509 / 441
- 25 °C to +80 °C  
-13 °F to +176 °F


## Characteristics

- high lateral stability
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing
- compatible with regular extension drawer slide FR 1052 SCC SMT
- available as heat-resistant version up to +110 °C (+230 °F)
- Easy Close Device (ECD) can be ordered optionally

## Mounting Type

- cabinet profile with bayonet mounting tabs and safety nose
- drawer profile without screw holes
- tool-less quick assembly of the cabinet profile

## Dimensions



Length		Extension				Weight		Item No.	Item No.
mm	inch	mm	inch	kg	lbs.	per set	PU 1	PU 2	
300	11.81	335	13.19	1.38	3.04	► 70450	► 70450GV		
350	13.78	385	15.16	1.46	3.22	► 70451	► 70451GV		
400	15.75	460	18.11	1.69	3.73	► 70452	► 70452GV		
450	17.72	510	20.08	1.93	4.26	► 70453	► 70453GV		
500	19.69	560	22.05	2.16	4.76	► 70454	► 70454GV		
550	21.65	610	24.02	2.40	5.28	► 70455	► 70455GV		
600	23.62	660	25.98	2.64	5.82	► 70456	► 70456GV		
650	25.59	710	27.95	2.87	6.33	► 70457	► 70457GV		
700	27.56	760	29.92	3.11	6.86	► 70458	► 70458GV		
750	29.53	810	31.89	3.37	7.43	► 70459	► 70459GV		

### Packing Unit

► in stock

PU 1 – Sets assembled per Box, all Lengths: 5

PU 2 – 50 Sets, all 6 profiles individually packaged, 10 boxes

(4 x 25 cabinet profiles LEFT/RIGHT, 4 x 25 middle profiles LEFT/RIGHT, 2 x 50 drawer profiles LEFT/RIGHT)